

# 30 HP

<b>Engine Model (Color)</b>	(a) E30DRS White (b) E30DRG Graphite (c) E30DRSL White (d) E30DRGL Graphite (e) E30GTEL Graphite (f) E30DTSL White (g) E30DGTL Graphite (h) E30DPSL White (i) E30DPGL Graphite
<b>Engine Type</b>	Inline 2-Cylinder E-TEC D.I.
<b>Bore x Stroke - in (mm)</b>	2.992 x 2.5 (76 x 64)
<b>Displacement - cu in (cc) L</b>	35.2 (577)
<b>Gear Ratio</b>	2.15:1
<b>Full Throttle RPM Range</b>	5500-6000 RPM
<b>Weight - lbs (kg)</b>	(a)(b) 150 (68) (c)(d) 154 (70) (e) 166 (75) (f)(g) 187 (85) (h)(i) 181 (82)
<b>Starting</b>	(a)(b)(c)(d) Rope (Electric Accessory) (e)(f)(g)(h)(i) Electric and Rope
<b>Controls</b>	Mechanical
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	56 Amps Total / 15 Amps Net Dedicated
<b>Steering</b>	(a)(b)(c)(d)(e)(f)(g) Tiller (Remote Available) (h)(i) Remote (Tiller Available)
<b>Trim Method</b>	(a)(b)(c)(d)(e) Manual Tilt (f)(g)(h)(i) Power Trim and Tilt
<b>Trim Range</b>	-4° to 16°
<b>Tilt Range</b>	65°
<b>Shaft Length - in (mm)</b>	(a)(b) 15 (381) (c)(d)(e)(f)(g)(h)(i) 20 (508)
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - qt (L)</b>	1.7 (1.6)
<b>Recommended Oil</b>	Evinrude / Johnson XD-100 Oil
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR / European Union



\* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.